

# → 4005 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating: "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection ensures optimal performance at all times | wide, 16" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut model (4014-2 SMC in US / 4005 SMC in Canada) meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on super micro-cut cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy chain drive and dust-proof gearbox housing | high quality wooden cabinet mounted on casters | convenient shred bin | 44 gallon shred volume

Dimensions (D x W x H): 23 1/4 x 25 1/4 x 39 3/4 inches, Shipping weight: 343 lbs. (strip-cut) / 378 lbs. (cross-cut) / 390 lbs. (super micro-cut).













"ECC" (Electronic Capacity Control) indicator monitors capacity levels during operation.

### → 4005 STRIP-CUT

Strip width	1/4''
Sheet capacity	50-52*
Security level	P-2
Feed opening	16"
Max. horsepower	2 1/8

#### → 4005 CROSS-CUT

Particle size	3/16" x 1 ½"
Sheet capacity	30-32*
Security level	P-4
Feed opening	16"

## Max. horsepower 2 1/8 → 4005 CROSS-CUT

Particle size	3/32"
Sheet capacity	18-20
Security level	P-5
Feed opening	16"
Max. horsepower	2 1/8

#### → 4014-2 SMC / 4005 SMC

x 5/8"

P	article size	1/32" x 3/16"
S	Sheet capacity	12-16*
S	Security level	P-7
F	eed opening	16"
١	Max horsenower	2 1/6

<sup>\*</sup> may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 1/2012.



20 amp. dedicated line required

3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508. fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 www.ideal-mbm.com

Dealer:

Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114