

# → 4810 D SEMI-AUTOMATIC CUTTER WITH DIGITAL DISPLAY

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | manual spindle clamp is guided on both sides to apply even pressure along entire cutting width | dual side guides on front and rear tables | spindle-guided back gauge with calibrated crank, narrow separations, and plastic gliders | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | stand with storage shelf

Dimensions (D x W x H):  $38 \frac{1}{4}$  x  $29 \frac{3}{4}$  x  $53 \frac{1}{2}$  inches, Shipping weight: 531 lbs.



## DIGITAL DISPLAY



The precise digital measurement readout for the back gauge can be displayed in cm or inches.

## OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

#### DUAL STDE GUIDES



Two side guides combined with the precision back gauge allow exact positioning of even the smallest stock sizes.

#### TRIUMPH 4810 D

ı	I INTUMEN 40	ת חד
	Cutting width	18 1/8"
	Cutting height	3"
	Narrow cut	1 1/4"
	Cutting length behind blade	17 11/16"
	Table length in front of blade	13 1/8"
	Motor	1.5 hp
	Power supply	115 V, 60

Hz

Dealer:



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com