

# → 4315 SEMI-AUTOMATIC CUTTER WITH DIGITAL DISPLAY

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | patented, lever-activated, fast-action clamp | precision side guide | spindle-guided back gauge with calibrated crank | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | optional stand (shown) or cabinet

Dimensions (D x W x H): 34 % x 25 % x 14 % inches (41 ½ H with stand, 42 ½ H with cabinet), Shipping weight: 196 lbs. (222 with stand, 291 with cabinet).



#### FRONT SAFETY GUARD



The hinged, transparent front safety guard is electronically controlled.

### DIGITAL DISPLAY



A digital measurement readout ensures exact positioning of back gauge.

#### FRONT BLADE CHANGE



The blade changing device covers edge of blade for safe handling.

## → TRIUMPH 4315

1 / 11(10)11 11 4010	
Cutting width	16 %''
Cutting height	1 ½"
Narrow cut	1 3/8"
Cutting length behind blade	17''
Table length in front of blade	9''
Motor	3/5 hr

115 V, 60 Hz

Power supply

Dealer:



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com