

# → 2240 DESKSIDE SHREDDER

transparent safety shield in the feed opening | automatic power cut-off when shredder head unit is removed from impact-resistant plastic shred bin | double protection against overheating | automatic start and stop controlled by photo cell | single, multifunction control switch with pilot light for stand-by, stop (off), and reverse | high quality, hardened steel cutting shafts take staples and paper clips (strip-cut model takes credit cards) | lifetime warranty on the cutting shafts | quiet and powerful single phase motor | durable gears enclosed in dust-proof housing | convenient handle for lifting shredder head unit from the shred bin | 5 gallon shred volume

Dimensions (D x W x H):  $8 \frac{1}{2}$  x  $13 \frac{1}{2}$  x  $17 \frac{3}{4}$  inches, Shipping weight: 16 lbs. (strip-cut) / 18 lbs. (cross-cut).



## MULTIFUNCTION SWITCH



Operation is controlled by a three-position rocker switch in combination with a photo cell for automatic start/stop.

### SAFETY SHIELD



A transparent safety shield keeps fingers, clothes, and other objects from entering the feed opening.

#### → 2240 STRIP-CUT

| Strip width     | 3/16"  |
|-----------------|--------|
|                 | (4 mm  |
| Sheet capacity  | 10-12  |
| Security level  | P-2    |
| Feed opening    | 8 3/4" |
| Max. horsepower | 1/5    |

#### → 2240 CROSS-CUT

| Particle size   | 1/8" x 1"<br>(3 x 25 mm) |
|-----------------|--------------------------|
| Sheet capacity  | 5-6*                     |
| Security level  | P-4                      |
| Feed opening    | 8 3/4"                   |
| Max. horsepower | 1/5                      |

<sup>\*</sup> may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 1/2011.



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com Dealer: